








| CARATTERISTICHE TECNICHE<br>Technical Features - Caracteristiques Techniques - Technische Eigenschaften<br>Technische Eigenschaften - Caracteristicas Tecnicas - Технические Характеристики   | NORMA<br>Standard - Norme<br>Norm - Norma - Норма | VALORI<br>Value - Valeur<br>Vorgabe - Valor - Средние                       |
|---|---|---|
|  <b>ASSORBIMENTO D'ACQUA (VALORE MEDIO IN %)</b><br>Water absorption (Average value expressed in %) - Absorption d'eau (Valeur moyenne en %)<br>Wasseraufnahme (Durchschnittswert in %) - Absorción de agua (Valor medio en %) Поглощение воды  | UNI EN ISO 10545/3<br><br>ASTM C373               | CONFORME<br><br>COMPLIANT   |
|  <b>RESISTENZA ALLA FLESSIONE</b><br>Modulus of rupture - Resistance a la flexion - Biegefestigkeit<br>Resistencia a la flexion - Прочность на изгиб  | SPESSORE<br>UNI EN ISO 10545/4                    | <b>6,5 mm</b> <b>10 mm</b><br>≥ 35 N/mm <sup>2</sup> ≥ 45 N/mm <sup>2</sup> |
|  <b>FORZA DI ROTTURA</b><br>Breaking strength - Résistance à la rupture - Bruchlast - Resistencia a la rotura - Разрывное усилие  | UNI EN ISO 10545/4<br><br>ASTM C648               | ≥ 700 N      ≥ 2000 N<br>250 Lbs      400 Lbs                               |
|  <b>RESISTENZA AL GELO</b><br>Frost resistance - Résistance au gel - Frostbeständigkeit<br>Resistencia a las heladas - Морозостойкость  | UNI EN ISO 10545/12<br><br>ASTM C1026             | CONFORME<br><br>UNAFFECTED  |
|  <b>RESISTENZA CHIMICA AD ALTE E BASSE CONCENTRAZIONI DI ACIDI E BASI</b><br>Chemical resistance to high and low acid and basic concentrations<br>Résistance chimique aux hautes et basses concentrations d'acides et de bases<br>Chemikalienfestigkeit bei hohen und niedrigen Konzentrationen von Säuren und Basen<br>Resistencia química con concentraciones altas y bajas de ácidos y bases<br>Химическая стойкость к высоким и низким концентрациям кислот и щелочей | UNI EN ISO 10545/13<br><br>ASTM C-650             | A - LA - HA<br><br>UNAFFECTED   |
|  <b>RESISTENZA ALLE MACCHIE</b><br>Stain resistance - Résistance aux taches - Fleckenbeständigkeit<br>Resistencia a las manchas - Стойкость к образованию пятен   | UNI EN ISO 10545/14                               | 5   |

| COEFFICIENTE DI ATTRITO   | NATURALE   | FULL LAPP.  |
|---|--|---|
|  Slip resistance - Coefficient de glissement - Rutschfestigkeit Barfußbereich<br>Coeficiente de atrito medio - Коэффициент трения | DIN 51130<br>DIN 51097<br>ANSI A 137.1- 2012<br>DCOF (SECTION 9.6)<br>B.C.R.A.<br>AS 4586: 2013<br>BS 7976-2: 2002<br>ENV 12633-2006 | R9<br>A<br>WET ≥ 0,42<br>-<br>≥ 0,40<br>-<br>-<br>- |

Per maggiori chiarimenti sui dati tecnici e sulla garanzia consultare il catalogo generale in vigore. - For further information on technical specifications, please consult our up-dated general catalogue. - Pour toutes informations supplémentaires sur les données techniques et sur les garanties, veuillez consulter le catalogue general en vigueur. - Für weitere Informationen über technische Daten und Garantie beziehen sie sich bitte auf den aktuellen Gesamtkatalog. - Para ulteriores informaciones sobre los datos técnicos y la garantía, vease el catalogo general en vigor. - Более подробную информацию о технических данных и гарантии смотрите в действующем сводном катал.



PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS. UL.COM/CG UL 2818



Min. 7,5%









## IMBALLI E PESI

Packing and Weight | Emballages et Poids | Verpackung und Gewicht | Embalajes y Pesos | Упаковка и Вес

| Formato<br>Size<br>Format<br>Format<br>Tamaño<br>Формат<br>cm | Spessore<br>Thickness<br>Épaisseur<br>Stärke<br>Espesor<br>Толщина<br>mm | Pz. x Mq.<br>Pieces x Sqm<br>Pcs / M <sup>2</sup><br>Stk. x Qm<br>Pzs x Mc.<br>Шт x Кв.М. | Pz. x Scat.<br>Pieces x Box<br>Pcs / Bte<br>Stk. x Krt.<br>Pzs x Caja<br>Шт x Кор. | Mq. x Scat.<br>Sqm x Box<br>M <sup>2</sup> / Bte<br>Qm x Krt.<br>Mc. x Caja<br>Кв.М. x Кор. | Peso x Scat.<br>Weight x Box<br>Poids / Bte<br>Gewicht x Krt.<br>Peso x Caja<br>Вес x Кор.<br>Kg | Scat. x Pal.<br>Boxes x Pal.<br>Bte / Pal.<br>Krt. x Pal.<br>Cajas x Pal.<br>Кор. x Подд. | Mq. x Pal.<br>Sqm x Pal.<br>M <sup>2</sup> / Pal.<br>Qm x Pal.<br>Mc. x Pal.<br>Кв.М x Подд. | Peso x Pal.<br>Weight x Pal.<br>Poids / Pal.<br>Gewicht x Pal.<br>Peso x Pal.<br>Вес x Подд.<br>Kg |
|---|--|---|--|---|--|---|--|--|
| 120x240 Nat. - Full Lappato                                   | 6,5  | 0,35  | 1  | 2,880   | 46,00  |   |  |  |
| 120x120 Nat. - Full Lappato                                   | 6,5  | 0,69  | 1  | 1,440   | 22,00  |   |  | vedi sotto - see below   |
| 60x120 Nat. - Full Lappato                                    | 10   | 1,39  | 2  | 1,440   | 33,17  | 36  | 51,84  | 1194   |
| 90x90 Full Lappato  | 10   | 1,23  | 2  | 1,620   | 36,54  | 24  | 38,88  | 877  |
| 30x60 Nat. - Full Lappato                                     | 10   | 5,56  | 6  | 1,080   | 24,69  | 40  | 43,20  | 988  |
| 7,5x30 Naturale   | 10   | 44,44   | 36   | 0,810   | 18,38  | 56  | 45,36  | 1029   |
| 31,9x28,3 Trama Naturale- Full Lappato                        | 10   | 11,08   | 5  | 0,450   | 10,40  | 60  | 27,00  | 624  |
| 30x30 Mosaico 5X5 Nat. - Full Lappato                         | 10   | 11,11   | 5  | 0,450   | 10,50  | 60  | 27,00  | 630  |
| 30x30 Mosaico 3X3 Nat. - Full Lappato                         | 10   | 11,11   | 5  | 0,450   | 10,42  | 60  | 27,00  | 625  |
| 30x30 Intrecci Nat. - Full Lappato                            | 10   | 11,11   | 5  | 0,450   | 10,50  | 60  | 27,00  | 630  |
| 28,2x29,1 Losanghe XS/XL Full Lappato                         | 10   | 12,19   | 5  | 0,410   | 10,30  | 60  | 24,60  | 618  |

## Slabs 120x120 - 120x240

| Articolo<br>Item<br>Reference<br>Artikel<br>Articulo<br>Артикула  | Dimensione (cm)<br>Size (cm)<br>Format (cm)<br>Format (cm)<br>Tamaño (cm)<br>Формат (cm) | Nr. Lastre<br>No. of Slabs<br>Nbre Dalles<br>Anz. Platten<br>N° de Placas<br>Кол. Плит | Mq. x Imballo<br>sqm per Pack<br>m <sup>2</sup> / Emballage<br>qm pro Verpackung<br>m <sup>2</sup> por embalaje<br>Кв.м. x упаковку | Peso Imballo (Kg)<br>Weight of Packaging (kg)<br>Poids Emballage (kg)<br>Gewicht Verpackung (kg)<br>Peso embalaje (kg)<br>Вес упаковки (кг) | Peso Imballo+Lastre (Kg)<br>Weight of Packaging + Slabs (kg)<br>Poids Emballage+Dalles (kg)<br>Gewicht Verpackung+Platten (kg)<br>Peso embalaje + placas (kg)<br>Вес упаковки + плит (кг) |
|---|--|--|---|---|---|
|  <b>120x120</b><br>Cassa - Crate - Caisse<br>Kiste - Caja - Ящик   |  |  |   |   |   |
|   | 139x139x36h  | 24   | 35,56   | 62,5  | 613,30  |
|  <b>120x240</b><br>Cassa - Crate - Caisse<br>Kiste - Caja - Ящик   |  |  |   |   |   |
|   | 136x266x18h  | 20   | 57,60   | 99  | 1020,6  |
|  <b>120x240</b><br>Cavalletto - A-Frame<br>Chevalet de transport - Transportgestell<br>Caballete - Подставка |  |  |   |   |   |
|   | 75x250x159,6h  | 40   | 115,20  | 163   | 2006,2  |

**EMIL**  
CERAMICA



USGBC  
MEMBER



ITALIA



CONFINDUSTRIA  
PER LA SOSTENIBILITÀ



CERTQUALITY  
SISTEMI DI GESTIONE  
CERTIFICATI



CERTQUALITY  
È MEMBRO DELLA  
FEDERAZIONE CISA